Unit B2, Stuart Road, Altrincham Business Park, Altrincham WA14 5GJ, United Kingdom. budenberg.co.uk sales@budenberg.co.uk +44 (0)161 777 7300

Model: 102NRF

The 102NRF range of Two Valve Manifolds provide a low cost Block and Bleed function to any instrument installation or application.

Based around the Budenberg 10N Needle Valve technology the versatility of these manifolds enable isolation, calibration and venting within a single unit thereby eliminating potential leak paths. The 102NRF range includes a full range of configurations and connections allowing them to be used on a full range of instrumentation including:

Transmitters, Gauges, Switches etc.

All units incorporate the Budenberg 10N high temperature, high pressure valve head assembly that is suitable for pressures up to 10,000 psig and temperatures up to 450 Degree Celsius.

These lightweight compact units can be readily manufactured, modified or configured to suit any individual application or customer requirement.

Basic Models

102NRF - Female process x Female instrument connections. For Direct transmitter mounting versions see additional datasheets

Material of Construction

Standard material is 316 St St to NACE MR 01-75. Units can be manufactured in a range of wetted parts materials including Monel and Hastelloy

Standard Connection Sizes

1/2" NPT Female process connection and female instrument connections, Vent connection is 1/4" NPT Female.

Other thread sizes available, contact sales for further details

Operating Pressure

10,000 psig Cold Working Pressure designated 102Nx

Operating Temperature

-20 to 240°C maximum for units fitted with PTFE stem packing -20 to 450°C maximum for units fitted with Graphoil packing For Cryogenic applications then a range of extended head versions are available

Dust Cap Identification

White Dust Cap indicates PTFE Stem Packing Black Dust Cap indicates Grahoil Stem Packing

Fire safe

Designed in compliance with BS 6755 Pt 2, API 10497, API 607

2 VALVE INSTRUMENT MANIFOLD REMOTE MOUNTING VERSION



Needle Valve Features

Stem Packing

Fully adjustable, dynamically responsive, multi ring 'gland sandwich' in either PTFE or Graphoil to resist all operating and processes. Budenberg offer 100% gland integrity for the lifetime of every valve

Stem Tip

Self centring, non rotating stem tip provides a true metal to metal valve seat whereby the material of the stem tip is one grade harder than the body thus resisting overtightening, preventing wear and guaranteeing a 100% bubble tight seat closure, first time, every time

Anti static, anti blow-out stems

True metal to metal Body / Bonnet joints. Bonnets are assembled with a locking pin to prevent accidental removal

Pressure & Temperature ratings as ANSI B 16.34 Class 2500


T' Bar operator with torque break feature

Certification

Material Certification to EN 10204 3.1b inc Mill Certificates Pressure Test Certificate CE Certificate of Conformity

Other testing / documentation / certification can be supplied dependant upon the contract / project requirements.


Dimensions Model: 102NRF



Model	Α	В	U	D	Е	F	Weight
62NRF	172mm	70mm	39mm	50.8mm	15.9mm	31.8mm	1 Kg

Model Number

Process



Notes

- Standard Screwed connections are NPT
- 2 For units on Cryogenic Service please contact our sales office
- 3 All wetted parts material conform to NACE MR 01-75 latest version
- For details of mounting brackets and other accessories please see additional datasheets
- 5 For interfacing onto other Transmitter types or configurations, please contact our sales office
- Multiple options can be specified if seperated by a forward slash symbol (/)

Specifications and dimensions in this leaflet, are subject to change without prior notice.



Budenberg Gauge Co. Ltd.

Unit B2, Stuart Road, Altrincham Business Park, Altrincham WA14 5GJ, United Kingdom.

Email: sales@budenberg.co.uk Website: www.budenberg.co.uk

Budenberg Gauge Pvt. Ltd. 299-300, IInd Main Road, Nehru Nagar,

Old Mahabalipuram Road (OMR) , Chennai - 600 096, Tamil Nadu , India

Tel : +91 44 24541074 Tel/Fax: +91 44 24541075 Email: sales@budenberg-gauge.in

Budenberg Gauge Asia Pacific Ltd

Unit 7A G/F Cheung Fat Ind Bldg 64-76 Larch St Tai Kok Tsui Kln Hong Kong

Tel: +852 3709 0020 Email: sales@budenberg-gauge.asia Budenberg Middle East LLC

PO Box 18980 Dubai United Arab Emirates

Tel: +971 4 2554740 Email: sales@budenberg-me.org